



Patmax Union Corporation

Tel No. : 886-2-29101925, 29101927 Fax No.: 886-2-29101946
 E-MAIL: patmax@ms16.hinet.net E-MAIL: patmax.corp@msa.hinet.net
 URL: http://www.patmax.com.tw URL: http://patmax.taiwantrade.com.tw

CABLE TIE

Catalogue No. EE-1812B
(2306)



MATERIAL: UL APPROVED POLYAMIDE 6.6, 94V-2 (PA66)
COLOR: NATURE COLOR, BLACK

Part.No	Length		Width		Max.Bundle Dia.		Min. Loop tensile strength		operating temperature	
	mm	inch	mm	inch	mm	inch	kgf	lbs	Max.	Min.
GT-80M	80	3.15	2.4	0.09	15	0.59	8.1	18	85° C (185° F)	-40° C (-40° F)
GT-100M	100	3.94	2.5	0.1	22	0.87	8.1	18	85° C (185° F)	-40° C (-40° F)
GT-120M	120	4.72	2.5	0.1	30	1.18	8.1	18	85° C (185° F)	-40° C (-40° F)
GT-140M	140	5.51	2.5	0.1	33	1.3	8.1	18	85° C (185° F)	-40° C (-40° F)
GT-160M	160	6.3	2.5	0.1	40	1.57	8.1	18	85° C (185° F)	-40° C (-40° F)
GT-200M	200	7.87	2.5	0.1	53	2.09	8.1	18	85° C (185° F)	-40° C (-40° F)
GT-250M	250	9.84	2.8	0.11	65	2.56	14	31	85° C (185° F)	-40° C (-40° F)
GT-300M	300	11.81	2.8	0.11	76	2.99	14	31	85° C (185° F)	-40° C (-40° F)
GT-120I	120	4.72	3.6	0.14	30	1.18	18.2	40	85° C (185° F)	-40° C (-40° F)
GT-140I	140	5.51	3.6	0.14	33	1.3	18.2	40	85° C (185° F)	-40° C (-40° F)

Part.No	Length		Width		Max.Bundle Dia.		Min. Loop tensile strength		operating temperature	
	mm	inch	mm	inch	mm	inch	kgf	lbs	Max.	Min.
GT-150I	150	5.91	3.6	0.14	35	1.38	18.2	40	85° C (185° F)	-40° C (-40° F)
GT-180I	180	7.09	3.6	0.14	44	1.73	18.2	40	85° C (185° F)	-40° C (-40° F)
GT-200I	200	7.87	3.6	0.14	53	2.09	18.2	40	85° C (185° F)	-40° C (-40° F)
GT-250I	250	9.84	3.6	0.14	65	2.56	18.2	40	85° C (185° F)	-40° C (-40° F)
GT-300I	300	11.81	3.6	0.14	76	2.99	18.2	40	85° C (185° F)	-40° C (-40° F)
GT-370I	370	14.57	3.6	0.14	102	4.02	18.2	40	85° C (185° F)	-40° C (-40° F)
GT-120ST	120	4.72	4.8	0.19	24	0.94	22.6	50	85° C (185° F)	-40° C (-40° F)
GT-160ST	160	6.3	4.8	0.19	38	1.5	22.6	50	85° C (185° F)	-40° C (-40° F)
GT-190ST	188	7.4	4.8	0.19	46	1.81	22.6	50	85° C (185° F)	-40° C (-40° F)
GT-200ST	200	7.87	4.8	0.19	50	1.97	22.6	50	85° C (185° F)	-40° C (-40° F)
GT-250ST	250	9.84	4.8	0.19	60	2.36	22.6	50	85° C (185° F)	-40° C (-40° F)
GT-280ST	280	11.02	4.8	0.19	70	2.76	22.6	50	85° C (185° F)	-40° C (-40° F)
GT-300ST	300	11.81	4.8	0.19	76	2.99	22.6	50	85° C (185° F)	-40° C (-40° F)
GT-370ST	370	14.57	4.8	0.19	102	4.02	22.6	50	85° C (185° F)	-40° C (-40° F)
GT-390ST	390	15.35	4.8	0.19	105	4.13	22.6	50	85° C (185° F)	-40° C (-40° F)
GT-430ST	430	16.93	4.8	0.19	110	4.33	22.6	50	85° C (185° F)	-40° C (-40° F)
GT-450ST	450	17.72	4.8	0.19	116	4.57	22.6	50	85° C (185° F)	-40° C (-40° F)
GT-530ST	530	20.87	4.8	0.19	140	5.51	22.6	50	85° C (185° F)	-40° C (-40° F)
GT-150HD	150	5.91	7.6	0.3	33	1.3	54.4	120	85° C (185° F)	-40° C (-40° F)
GT-200HD	200	7.87	7.6	0.3	50	1.97	54.4	120	85° C (185° F)	-40° C (-40° F)
GT-250HD	250	9.84	7.6	0.3	65	2.56	54.4	120	85° C (185° F)	-40° C (-40° F)

Part.No	Length		Width		Max.Bundle Dia.		Min. Loop tensile strength		operating temperature	
	mm	inch	mm	inch	mm	inch	kgf	lbs	Max.	Min.
GT-300HD	300	11.81	7.6	0.3	76	2.99	54.4	120	85° C (185° F)	-40° C (-40° F)
GT-370HD	370	14.57	7.6	0.3	102	4.02	54.4	120	85° C (185° F)	-40° C (-40° F)
GT-430HD-S	430	16.93	7.6	0.3	123	4.84	54.4	120	85° C (185° F)	-40° C (-40° F)
GT-450HD-S	450	17.72	7.6	0.3	132	5.20	54.4	120	85° C (185° F)	-40° C (-40° F)
GT-540HD-S	533	20.98	7.6	0.3	140	5.51	54.4	120	85° C (185° F)	-40° C (-40° F)
GT-430HD	430	16.93	9	0.35	120	4.72	79.4	175	85° C (185° F)	-40° C (-40° F)
GT-530HD	526	20.71	9	0.35	140	5.51	79.4	175	85° C (185° F)	-40° C (-40° F)
GT-630HD	610	24.02	9	0.35	187	7	79.4	175	85° C (185° F)	-40° C (-40° F)
GT-710HD	710	27.95	9	0.35	190	7.48	79.4	175	85° C (185° F)	-40° C (-40° F)
GT-780HD	778	30.55	9	0.35	228	8.98	79.4	175	85° C (185° F)	-40° C (-40° F)
GT-830HD	815	32.09	9	0.35	239	9.41	79.4	175	85° C (185° F)	-40° C (-40° F)
GT-920HD	916	36.06	9	0.35	263	10.35	79.4	175	85° C (185° F)	-40° C (-40° F)
GT-1220HD	1220	48.03	9	0.35	365	14.37	79.4	175	85° C (185° F)	-40° C (-40° F)
GT-1530HD	1530	60.24	9	0.35	460	18.11	79.4	175	85° C (185° F)	-40° C (-40° F)